



DESCRIPTION

- Aqueous phase bituminous emulsion that adheres well to most clean surfaces.
- Once dry, it constitutes a waterproof barrier that is resistant to a large number of chemical agents and protects the material to which it has been applied.

USES

- Protection of foundations and below-ground rendered surfaces.
- Protection of below-ground materials (concrete, wood, metal).
- Bonding of insulating materials (e.g. cork slabs, mineral wool).
- Protection of below-ground materials (concrete, wood, metal).
- Compatible with the PAREXLANKO EWI range – for bonding insulating material to substrates already covered with a bituminous coating.

SPECIFICATIONS

- **Appearance:** dark brown paste
- **Density at 20°C:** 1.00 ± 0.05
- **Drying time at 20°C:**
 - surface dry: 2 hours
 - fully dry: 24 hours
- **Dry extract:** 57 ± 3%
- **Penetrability at 25°C:** 270 ± 30 l/10 mm (NF T 60119)
- **Permeability to steam:** 0.8 g/m²/24 hrs for 1.7 kg/m² (NF X 41001)

INSTRUCTIONS

- **SUBSTRATE PREPARATION**
 - Remove all loose and flaking parts.
 - Clean off all traces of mud, dust and grease.
 - Dampen the surface if necessary (porous substrates). Best bonding results are obtained on surfaces which are damp to the touch, but not saturated with water.
 - Build a mortar chamfer at the base of the walls.

■ PRODUCT PREPARATION

- Stir the paste until contents are evenly mixed (except for the case of bonding of insulating materials).

■ APPLICATION

Bonding of insulating materials

- Apply a series of dabs or beads of 201 LANKOBLACK PÂTEUX to the reverse side of the insulating material.
- Foundations and surface protection
- On porous substrates, dilute 1st coat with 30% water
- Apply 2 cross layers with a smoothing trowel or brush. The first coat must be completely dry prior to re-coating
- On metal apply a minimum of 2 coats by brush or spatula.

■ CLEANING OF TOOLS AND EQUIPMENT

- Fresh: with water
- Dry: with white spirit.

PRODUCT FEATURES

- ▶ Protection of foundations and below-ground rendered surfaces
- ▶ Bonding of insulating materials
- ▶ Anti-corrosion protection
- ▶ Resistant to water, alcohol and most acids and diluted bases

CONSUMPTION

- ▶ Bonding insulating materials: 0.6 to 0.8 kg/m²
- ▶ Surface protection: 1.5 to 2 kg/m² for 2 coats

PACKAGING

- ▶ 25 kg bucket
- ▶ 5 kg bucket

STORAGE

- ▶ **24 months** from date of manufacture if store in unopened original packaging protected from frost and high temperatures

WARRANTY

- ▶ Manufacturer's liability

TECHNICAL ASSISTANCE. ParexGroup S.A. will, on request, provide information and assistance to companies in relation to the specific use of a product. Such assistance shall not be assimilated with structural design and conception, nor the compliance of substrates, nor as a control of usage rules in force.

TECHNICAL DATA SHEET ISSUED - September 2017

The information provided in this document results from our knowledge of the products and our experience. Prior to application, customers and users are requested to check that they are in possession of the latest version of this document. Please check for updates at www.parexlanko.com

PAREXGROUP S.A. 19 place de la Résistance - CS 50053
92445 Issy-les-Moulineaux Cedex - Tél. (33) 01 41 17 20 00
Technical information : 0 826 08 68 78 (0.15 €/min + phone call price)

PAREXLANKO

201 LANKOBLACK PÂTEUX

PRECAUTIONS

- Do not use in temperatures below + 5°C or in rainy or foggy conditions.
- Do not apply to a frozen, non-absorbent substrate.
- Do not bank up the surrounding area until the product is fully dry.
- Protect from impacts.
- Protect the coated surface from direct sunlight.
- Use in compliance with building regulations in force regarding buried masonry (e.g. for France NF P 10-202 and DTU 20.1)
- 201 LANKOBLACK PÂTEUX is not intended to withstand pressurised water.
- Non-resistant to hydrocarbons, oils and solvents.
- Store away from direct sunlight.
- Refer to the Safety Data Sheet.