



PRODUCT FEATURES

- ▶ Protection of below-ground parts of coated structures
- ▶ Protection of metal against corrosion
- ▶ Can be applied by spraying

CONSUMPTION

- ▶ 0.3 to 0.5 litre/m² for 2 coats, depending upon substrate porosity

PACKAGING

- ▶ 5 litre bucket
- ▶ 25 litre drum

STORAGE

- ▶ **24 months** from date of manufacture if store in unopened original packaging protected from frost and high temperatures

WARRANTY

- ▶ Manufacturer's liability

211 LANKOBLACK VERNIS



DESCRIPTION

- Black, bituminous, solvent-phase paint that forms a continuous, highly-adhesive waterproof film on the substrate.
- Waterproofs the surface so as to prevent rising damp and protect the substrate from aggressive water.
- **211 LANKOBLACK VERNIS** also protects steel reinforcement elements against corrosion.

USES

- Additional waterproofing of concrete and coated masonry foundations.
- Protection of underground parts of metal structures.

SPECIFICATIONS

- **Ready-to-use paint**
- **Colour:** black
- **Density:** 0.95 ± 0.025
- **VOC content:** 60 % ± 5%
- **Dry extract:** 65 ± 3%
- **Viscosity at 25°C:** 60 ± 20s (EN ISO 2431)
- **Flash point:** 45°C ± 2°C

INSTRUCTIONS

- **SUBSTRATE PREPARATION**
 - Remove all loose and flaking parts.
 - Build a mortar chamfer at the base of the walls.
 - Clean off all traces of mud, dust and grease.
- **PRODUCT PREPARATION**
 - Stir well until evenly distributed.

APPLICATION

- **211 LANKOBLACK VERNIS** is applied in two cross-coats to dry substrates by brush or broom.
- The 2nd coat is applied as soon as the 1st has dried completely (drying time = 3 to 6 hours depending on climatic conditions).
- Spray application: use an Airless gun (nozzle 515 or 517) or a conventional liquid paint gun & nozzle. In the latter case, a mask must be worn (A1 or A2 indoors, P3 outdoors).
- Clean tools with white spirit.

TECHNICAL ASSISTANCE. ParexGroup S.A. will, on request, provide information and assistance to companies in relation to the specific use of a product. Such assistance shall not be assimilated with structural design and conception, nor the compliance of substrates, nor as a control of usage rules in force.

TECHNICAL DATA SHEET ISSUED - September 2017

The information provided in this document results from our knowledge of the products and our experience. Prior to application, customers and users are requested to check that they are in possession of the latest version of this document. Please check for updates at www.parexlanko.com

PAREXGROUP S.A. 19 place de la Résistance - CS 50053
92445 Issy-les-Moulineaux Cedex - Tél. (33) 01 41 17 20 00
Technical information : 0 826 08 68 78 (0.15 €/min + phone call price)

PAREXLANKO

PRECAUTIONS

- As for all solvent-based products, suitable precautions must be taken.
- Do not use in temperatures below + 5°C or in rainy or foggy conditions.
- Do not apply to a frozen substrate.
- Do not bank up the surrounding area until the product is fully dry.
- Protect from impacts.
- Use in compliance with building regulations in force regarding buried masonry (e.g. for France NF P 10-202 and DTU 20.1)
- **211 LANKOBLACK VERNIS** is not intended to withstand pressurized water.
- Non-resistant to hydrocarbons, oils and solvents.
- Refer to the Safety Data Sheet.