



### PRODUCT FEATURES

- ▶ Single-component
- ▶ Floor protection and decoration
- ▶ Stops the phenomenon of «fluffing»

### CONSUMPTION

- ▶ 6 to 10 m<sup>2</sup>/litre/coat

### PACKAGING

- ▶ 5 litre bucket

### STORAGE

- ▶ **24 months** from date of manufacture if stored in unopened original packaging protected from frost, high temperatures and heat sources

### WARRANTY

- ▶ Manufacturer's liability

# 438 LANKOFLOOR PEINTURE



### DESCRIPTION

- Ready-to-use, single-component, solvent-phase urethane-alkyd paint designed for the protection and decoration of floors.

### USES

#### INTERIOR - EXTERIOR

- Residential basements
- Stairs
- Balconies, loggias
- Private car parks and garages

### SPECIFICATIONS

- **Appearance:** silky
- **Colours:** sand, cement grey, silver
- **Density at 20°C:** 1.15 ± 0.1 at + 20°C
- **VOC content:** 499 g/l max. (directive 2004/42/CE)
- **AFNOR Classification:** NF 36.005 - Family I - Class 4a

### INSTRUCTIONS

#### SUBSTRATE PREPARATION

##### New screed

- Concrete must be perfectly dry (at least 28 days old), clean and free of all traces of surface laitance.

##### Old screed

- Clean thoroughly, removing all traces of grease and oil, repair cracks and remove dust.
- In all cases, please refer to and abide by reference documents in force for this product category (e.g. for France, DTU 59-3 «Floor paints»).

### APPLICATION

- Stir well to ensure even distribution.
- Apply with a brush or roller.
- One coat is sufficient to provide dust protection.
- Two coats will produce the appearance of a silk paint.
- On raw and absorbent substrates, dilute the 1<sup>st</sup> coat with 10-15% white spirit. Subsequent coats do not need to be diluted.
- If the interval between coats has exceeded 72 hours, the surface must be lightly sanded.
- Key interval data at + 20°C / 60% RH
  - dust-free: 1 to 2 hours,
  - touch dry: 3 to 4 hours,
  - coverable: between 16 and 48 hours
  - Final total resistance: 7 days.

### Colour chart

Cement Grey

Silver

Please note that printing processes do not allow an exact reproduction of colours. Slight differences may also occur between different batches and according to the nature of the substrate.

**TECHNICAL ASSISTANCE.** ParexGroup S.A. will, on request, provide information and assistance to companies in relation to the specific use of a product. Such assistance shall not be assimilated with structural design and conception, nor the compliance of substrates, nor as a control of usage rules in force.

#### TECHNICAL DATA SHEET ISSUED - September 2017

The information provided in this document results from our knowledge of the products and our experience. Prior to application, customers and users are requested to check that they are in possession of the latest version of this document. Please check for updates at [www.parexlanko.com](http://www.parexlanko.com)

**PAREXGROUP S.A.** 19 place de la Résistance - CS 50053  
92445 Issy-les-Moulineaux Cedex - Tél. (33) 01 41 17 20 00  
Technical information : 0 826 08 68 78 (0.15 €/min + phone call price)

# PAREXLANKO

### PRECAUTIONS

- Keep premises well-ventilated during application.
- Temperature range for use: + 10°C to + 30°C.
- Hygrometry: < 70%.
- Substrate must be dry (humidity < 4%).
- Clean tools with 725 LANKODILPOX.
- Suitable Personal Protection Equipment must be worn
- Refer to the Safety Data Sheet.