

## FAÇADES

### COMPLEMENTARY PRODUCTS, TOOLS AND ACCESSORIES

#### ORGANIC PASTE SETTING ACCELERATOR



#### PRODUCT FEATURES

- ▶ Accelerates setting of PARITÉ+ paste base coat and decorative organic finish coats from the REVLANE+ range in cold & damp conditions
- ▶ Enables work to continue in temporarily difficult weather conditions

#### CONSUMPTION

- ▶ 1 to 2 kg per 25 kg bucket

#### PACKAGING

- ▶ 1 kg box

#### STORAGE

- ▶ **12 months**

from date of manufacture if stored in unopened original packing in dry, conditions

#### WARRANTY

- ▶ Manufacturer's liability

**TECHNICAL ASSISTANCE:** ParexGroup S.A. will, on request, provide information and assistance to companies in relation to the specific use of a product. Such assistance shall not be assimilated with structural design and conception, nor the compliance of substrates, nor as a control of usage rules in force.

**TECHNICAL DATA SHEET ISSUED - September 2017**

The information provided in this document results from our knowledge of the products and our experience. Prior to application, customers and users are requested to check that they are in possession of the latest version of this document. Please check for updates at [www.parexlanko.com](http://www.parexlanko.com)

**PAREXGROUP S.A.** 19 place de la Résistance - CS 50053  
92445 Issy-les-Moulineaux Cedex - Tél. (33) 01 41 17 20 00  
Technical information : 0 826 08 68 78 (0.15 €/min + phone call price)

# PAREXLANKO

# PARITÉ+ ACCÉLÉRATEUR

EXTERNAL  
WALL  
INSULATION  
**PAREXLANKO**



#### DESCRIPTION

- White powder additive intended for accelerating the setting of **PARITÉ+\*** fire-resistant paste and **REVLANE+ IGNIFUGÉ TALOCHÉ\***, **REVLANE+ IGNIFUGÉ RIBBÉ\*** and **REVLANE+ SILOXANÉ IGNIFUGÉ TF\*** decorative finish coats.

#### USES

##### PERMISSIBLE SUBSTRATES

- For full details of permissible and non-permissible substrates please refer to the Technical Data Sheets for the following products: **PARITÉ+\***, **REVLANE+ IGNIFUGÉ TALOCHÉ/RIBBÉ\*** and **REVLANE+ SILOXANE IGNIFUGÉ TF\***.

#### SPECIFICATIONS

- White powder composed of hydraulic binders and mineral filler

#### INSTRUCTIONS

##### PRODUCT PREPARATION

- Mix 1 to 2 kg of **PARITÉ+ ACCELERATEUR** with one 25 kg bucket of pure paste.
- Machine-mix on slow speed.
- Leave to stand for 5 min approx prior to use.
- Paste to which the accelerator has been added must be used within 1 hour of mixing.

#### CONSUMPTION

- 1 to 2 kg per 25 kg bucket of pure paste according to atmospheric conditions.

\* Please refer to the relevant product data sheet.

#### PRECAUTIONS

- For professional use only.
- Not for use in normal atmospheric conditions (i.e. T above + 15°C and RH below 65 %) or conditions unsuitable for application of finish coats (e.g. frozen substrate, risk of frost, continuous rainfall, etc...).
- Please refer to the Safety Data Sheet.